

Global 2 - U.K (GBP)

Coinco's dependable four-tube changer is now more reliable and has new value-added features

Features and Benefits

- Easy set up and service using built-in diagnostics facilities and display
- Modular construction allows easy service without tools
- Accurate reporting of tube coin quantities
- Four change tubes for extended change giving
- Simple float-level setting
- **New** Executive audit support
- User definable payout configuration with easily removable coin tubes
- Easy access to tubes, via hinged cover
- High speed payout
- MDB Interface as Standard
- **New** support for either an MDB cashless device or an MDB bill acceptor (*Executive model only*)
- Accepts up to 32 coins or tokens
- IRDA interface available



The **Global 2** coin changer is a robust yet sophisticated unit that offers high performance and fast, trouble-free coin validation and handling for a range of vending applications.

Coupling the Executive model of the **Global 2** coin changer with either an MDB cashless device or an MDB bill acceptor offers both a flexible and reliable solution to the majority of payment system requirements. The addition of support for executive audit enables centralized MIS information collection.

The modular **Global 2** coin changer offers a true 'Plug & Play' capability whether being used in Executive (Protocol A), MDB, Single/Four-price (Electro-mechanical), BDV or L/L+.

CAE - EUROPE

UK (European HQ)
T: +44 (0) 1342 315724
F: +44 (0) 1342 313850
E: europe@coinco.com

Help Desk:
+44 (0) 1342 311130

France
T: 33.1.56.48.05.05
F: 33.1.56.48.05.06
E: france@coinco.com

Germany
T: 49 2154 205000
F: 49 2154 205002
E: germany@coinco.com

Technical Data Summary

Payout Options

GBP- 801

Coins Paid out 20p - 5p - 10p - 50p

Coins Accepted 5p - 10p - 20p - 50p - £1 - £2 / Euro ready

GBP - 802

Coins Paid out 20p - 5p - 1p - 2p

Coins Accepted 1p - 2p - 5p - 10p - 20p - 50p - £1 / Euro ready

Dimensions

Height	379 mm (base to end of escrow lever)
Width	139 mm
Depth	83 mm

Weight

Weight	2.5 kg
--------	--------

Environmental

Operating Temperature	-18° to 65° (Celsius)
Storage Temperature	-30° to 72° (Celsius)
Relative Humidity	20% to 98% (Non-condensing)

Coin/Token Size Range

Diameter	15.00 to 33.50 mm
Thickness	1.02 to 3.10 mm

Operating Orientation

Vertical +3 degrees

Communications Interfaces

Executive (Protocol A), MDB, Single/Four-price (Electro-mechanical),
BDV, L/L+, DEX/UCS

Electrical Interface

Voltage: Nominal

Current: Typical (idle)

Executive (Protocol A)	24V AC	0,275A
MDB	34V DC	0,080A
Single/Four-price (Electro-mechanical)	24V AC	0,200A
	120V AC	0,225A
	220V-240V AC	0,080A
BDV	24V DC	0,275A
L/L+	24V DC	0,160A

Coin Acceptors Europe Ltd 2005. All rights reserved

This publication is issued to provide outline information only which (unless agreed in writing by Coin Acceptors Europe Ltd) may not be used, applied or reproduced for any purpose, or form part of any order or contract or be regarded as a representation relating to the product or service concerned. Coin Acceptors Europe Ltd reserves the right to alter without notice the specification, design or conditions of supply of any product or service.

Coinco is a registered trademark of Coin Acceptors Inc, as is Global 2.

Publication code: CAE/EN/002/GBP

For further payout combinations or to add tokens please contact your nearest Coin Acceptors office either by telephone, e-mail, or fax. Alternatively, you can visit our website where you will find a wide range of information on our company and products

www.coinco-europe.com

GLOBAL 2

