

RT500

The RT500 from IMI Cornelius builds on our long established reputation for performance, reliability and support. The RT500 slide top refrigerator combines enhanced levels of quality and refinement with practical, innovative features for ease of functionality and usability.

These include:

- Forced air-cooling for even temperature distribution
- Easy access slide top lid for rapid service
- Complete with castors allowing the unit to be moved easily even when full
- Large bottle capacity
- Part of a complementary range of units
- Can be banked side by side





Performance:

Pull down:	24°C to 6°C in 9.5 hours
Capacity:	330ml cans 108
	330ml bottles 70
	500ml cans 88

Max. working ambient temp:	32°C
Thermostat temp. range:	+2°C - +6°C

Dimensions:

Height Packed:	845mm
Width Packed:	530mm
Depth Packed:	550mm
Weight unloaded:	27 Kg

Electrical:

Mains supply:	220v 50Hz
Mains cable:	2 metres
Run current:	1.1 amps
Start current:	1.2 amps
Power consumption:	242 watts
Fuse rating:	13 amps

Refrigeration:

Compressor size:	3.68cc
Compressor duty:	139 watts (-10°C)
Condenser fan:	5 watts
Refrigerant type:	R134a
Temperature Control:	Mechanical (adjustable)

Siting:

Unit can be:	Boxed in, banked side by side
Vented:	Keep vents free from obstruction

Materials:

Cabinet:	Stainless Steel and Plastic coated Steel with PU foam insulation
Doors:	Stainless Steel

Compliance to standards and legislation
 EMC Directive 89/336/EEC as amended by 92/31/EEC Low Voltage Directive
 73/23/EEC as amended by 93/68/EEC.

This product complies with the current requirements of the EMC Directive.

IMI Cornelius reserves the right to modify the details in the publication as products and specifications are updated and improved. All data contained in this literature is correct at time of print. To ensure technical data is accurate please contact IMI Cornelius prior to placing your order.

