

# Statesman

The Statesman bottle cooler from IMI Cornelius builds on our long established reputation for performance, reliability and support. The Statesman visi-cooler is designed to provide a long and reliable working life, working hard for you and your money.

The Statesman offers maximum visibility and ensures consistent, accurate temperatures. Supplied complete with fully adjustable plastic coated shelves so they can be configured to suit your requirements and the units are available with a blackboard or illuminated panel to help promotions and draw attention.

Features include:

- Plug and play low maintenance design
- Front breathing refrigeration system, allowing unit to be completely built in
- Efficient forced air cooling ensuring faster and uniform chilling
- Superb internal illumination delivering maximum brand visibility, increasing impulse purchasing
- Available with a chalkboard or illuminated advertising panel





**Performance:**

Pull down: 24°C to 6°C in 15 hours

Capacity: 330ml cans: 620  
 330ml bottles: 280  
 500ml cans: 400

Maximum ambient temperature: 32°C  
 Thermostat temperature range: +2°C>+8°C

**Dimensions:**

Height packed: 1980mm  
 Width packed: 1190mm  
 Depth door open: 1190mm  
 Depth packed: 750mm  
 Weight unloaded: 160kg  
 Quantity of shelves: 4  
 Shelving options: None

**Electrical:**

Mains supply: 230v AC, 50 Hz  
 Mains cable: 2m  
 Run current: 4 amps  
 Start current: 16 amps  
 Power consumption: 615 watts  
 Fuse rating: 10 amps

**Refrigeration:**

Compressor size: 12cc  
 Compressor duty: 421 watts @ -10°C  
 Evaporator fan: 2 x 10 watt  
 Condenser fan: 5 watt  
 Refrigerant type: R134a  
 Temperature Control: Mechanical (adjustable)  
 Defrost: 20 minutes off every 4 hours

**Lighting:**

	Cabinet interior	Merchandiser plaque
Quantity:	1	1
Type:	Fluorescent	Fluorescent
Size:	48" x 40 watts	36" x 30 watt
Starter:	EFA 220-240 (4/65W) x 2	EFA 220-240 (4/65w) x 2
Choke:	40/240v/50Hz	30/240v/50Hz

**Siting:**

Unit can be: Boxed in and banked side by side  
 Vented: From the front of the grille

**Materials:**

Cabinet: Plastic coated or painted steel with PU foam insulation  
 Doors: Aluminium extrusion with toughened double glazing

Compliance To Standards And Legislation  
 EMC Directive 89/336/EEC as amended by 92/31/EEC Low Voltage Directive 72/23/EEC as amended by 93/68/EEC.

This product complies with the current requirements of the EMC Directive.

IMI Cornelius reserves the right to modify the details in the publication as products and specifications are updated and improved. All data contained in this literature is correct at time of print. To ensure technical data is accurate please contact IMI Cornelius prior to placing your order.

